



Home > Product > Media Conversion > Unmanaged Media Converter Chassis > MC-1500

Print Version

Products

LAN Switches

Power over Ethernet

Industrial Ethernet

Media Conversion

- Web Smart / Smart Gigabit Media Converter
- Web Smart / Smart Fast Ethernet Media Converter
- Standard Gigabit Media Converter
- Standard Fast Ethernet Media Converter
- Ethernet Extender
- Serial over Ethernet Converter
- Unmanaged Media Converter Chassis
- Managed Media Converter Chassis
- Video Optical Transmission

Passive Optical Network

Wireless LAN

IP Surveillance

IP Telephony

Broadband Communication

Home Automation

Network Security

Network Peripheral



MC-1500

15-Slot Media Converter Chassis



Overview Applications Key Features Specifications Download Related Products

<b>Slot</b>	15 open slots; 27 x 95 x 71 mm (W x D x H)
<b>Dimensions (W x H x D)</b>	440 mm x 103 mm x 180 mm, 2.4U height
<b>Enclosure</b>	Metal
<b>Power Requirement</b>	100-240V AC, 1.8A, 50/60Hz
<b>Power Output</b>	+5V DC per slot, 1A minimum
<b>DC Output</b>	+5V DC (+/-1%) per slot
<b>LED Indicators</b>	3, Power, Fan A, Fan B (On: operating; Off: device or fan fail)
<b>Environment</b>	Temperature: 0~50 degrees C (operating); -20~70 degrees C (storage) Humidity: 0~90% (non-condensing)
<b>Compliance</b>	FCC Class A, CE-mark

Ordering Information

**MC-1500** 19-inch Media Converter Chassis with 15 Slots

Partner Login

User Name:

Password:

Top

