



Home > Product > Media Conversion > Unmanaged Media Converter Chassis > MC-1500R

Print Version

- Products**
- LAN Switches
 - Power over Ethernet
 - Industrial Ethernet
 - Media Conversion
 - Web Smart / Smart Gigabit Media Converter
 - Web Smart / Smart Fast Ethernet Media Converter
 - Standard Gigabit Media Converter
 - Standard Fast Ethernet Media Converter
 - Ethernet Extender
 - Serial over Ethernet Converter
 - Unmanaged Media Converter Chassis
 - Managed Media Converter Chassis
 - Video Optical Transmission
 - Passive Optical Network
 - Wireless LAN
 - IP Surveillance
 - IP Telephony
 - Broadband Communication
 - Home Automation
 - Network Security
 - Network Peripheral



MC-1500R

15-Slot Media Converter Chassis (AC Power)



- Overview
- Applications
- Key Features
- Specifications
- Download
- Related Products

Hardware Specifications

Dimensions (W x D x H)	438 x 200 x 103 mm, 2.4U high
Slot	15 open slots (Slot Dimensions (W x D x H) 27 x 95 x 71 mm,)
LED	Power 1, Power2, Fan1, Fan2
Fan	2 x Fan
Weight	4.3kg
Power Requirements	100~240V AC, 3.3A, 50-60Hz
Power Output	Each slot 5V DC 1A
Power Consumption	10 watts / 34.1BTU (System only) 80 watts / 272BTU (Full loading)
Operating Environment	0~50 degrees C, 5%~90%RH
Storage Environment	-20~70 degrees C, 5%~90%RH
Emission	FCC Class A, CE mark

Ordering Information

MC-1500R	15-Slot Media Converter Chassis (AC Power)
MC-15RPS130	130W Redundant Power Supply, 100-240V AC
MC-15RPS48	Redundant Power Supply, -48V DC

Partner Login

User Name:

Password:

Top